



## **CB-SV-12**

Smart Submittal for Soffit Mounted Vertical **Downward Discharge Chilled Beam** 





|  |              |  | 100g &  | Back                                       |
|--|--------------|--|---|--|
| -  | t            |  | _   | 81/2"                                      |
| SV MODEL  12" Tall, 8.5" Wide (12)   |              | <b>UNIT SIZE</b> (see page 2 fo  |   | Right hand piping shown Left hand opposite |
| COIL CIRCUITS  2 pipe 2 Row (2)  4 pipe 2 Row (4)  COIL CAPACITY  Single circuit coil for 0.5-1.50gpm (  Dual circuit coil for 1.50-2.4gpm (D  |              | 3' nom. L = 36" 4' nom. L = 48" 5' nom. L = 60" 6' nom. L = 72"  INLET SIZE (see page 2 3" nom. (DØ = 2%" 4" nom. (DØ = 3%" 5" nom. (DØ = 4%")   | (3FT)<br>(4FT)<br>(5FT)<br>(6FT)<br>t for details)<br>Round |  |
| 5%" OD (for sweat connection by others) (N)  ½" MNPT (for field connection to ½" FNPT fittings) (M)*  INDUCTION SELECTION  6R 4R 3R 2R  COIL PIPING HANDING (see page 2 for details)  Coil Left Hand Side (L) (as shown above)  Coil Right Hand Side (R) (Coil Opposite Side)  INLET LOCATION (see page 2 for details)  Left Side (L)  Right Side (R)  Back (B)  Top (T)  Combo Left and Right (C) |              | COLOR SELECTION  No Finish (0)  COIL FINISH  Self finish (0) Flat black (F)*  INSULATION No insulation (0) External insulation ( INLET SHAPE Round (0) Oval (V) MOUNTING BRACKET Fixed (0)  CONDENSATE DRAIN With 1/2" Fitting (0) | TS<br>N   |  |
| Tags: QTY:   |              | SPECIFICATIONS (also see s   | Ivanized steel (u   | ,  |
|  |              | -Balancing /commissioning port no<br>-Vertical discharge grille by others<br>-Return plenum/ transition, cabine  | s<br>et casing, and gr                                      | ille by others                             |
|  |              | *Indicates an added cost it<br>-Additional lead time may be req<br>-Contact Carson Solutions for mo  | uired   |  |
| Project:   |              |  |   | Submittal Date:                            |
| Location:  | Product Code | CB-SV-*-***-*-*-*X*-*-*  | ***   | Page                                       |



952.525.2050


www.carsonsolutions.com info@carsonsolutions.com



# **CB-SV-12**

Smart Submittal for Soffit Mounted Vertical Downward Discharge Chilled Beam


#### Side Inlet Locations



### **Back Inlet and Fixed Bracket Mounting Locations**


| Beam   | L    | Α      |  |
|--------|------|--------|--|
| Length | (in) | (in)   |  |
| 2'     | 24   | 23 1/4 |  |
| 3'     | 36   | 35 1/4 |  |
| 4'     | 48   | 47 1/4 |  |
| 5'     | 60   | 59 1/4 |  |
| 6'     | 72   | 71 1/4 |  |

| Inlet   | D (in)        |  |  |  |  |
|---------|---------------|--|--|--|--|
| 3"      | 2 3/4         |  |  |  |  |
| 4"      | 3 3/4         |  |  |  |  |
| 5" Oval | 2 1/2 x 6 1/4 |  |  |  |  |




#### **Piping Configurations**

- -2 Pipe Coil Connections
- -Right Hand Piping Shown
- -Left Hand Opposite Side



- -4 Pipe Coil Connections
- -Right Hand Piping Shown
- -Left Hand Opposite Side



**Project:** Carson Samples

Submittal Date: 6/18/2023

Location: Golden Valley, MN

Page 10



952.525.2050

www.carsonsolutions.com info@carsonsolutions.com