

CB-H24 - 2S2M - 2W - 4R - P - R - STD - 4 X 5 - 0 - 0 0 0 0 0

2 - Pipe
4 - Pipe

S - Single Circuit SC
D - Dual Circuit DC

2 - 1/2" Pipe

M - Male NPT Fittings
N - No Fittings Straight Pipe

Length
2FT
4FT
6FT
8FT

Inlet Diameter
4"
5"
6"
8" (requires tall plenum)

(STD, TG1, TG2, EXP) - Border Style

T - Top Handing
R - Right Handing
L - Left Handing

P - Perforated Grille

Induction Ratio 2:1, 3:1, 4:1, 6:1
(2R, 3R, 4R, 6R) - Nozzle Type
2R recommended tall plenum

2W - 2 Way Throw
1S - 1 Way Throw, Same Side Inlet
1A - 1 Way Throw, Away Side Inlet

0 - Galvanized Plenum
P - Painted Plenum
0 - Fixed Hanging Bracket
0 - Standard Round Inlet
0 - Standard No Insulation
E - External Insulation
0 - Self Finish Coil
F - Flat Black Coil
0 - RAL9010 30% Gloss
RX - Special Color

Sample Codes:

- CB-H24-2S2M-2W-2R-P-T-STD-4X6-0-00000
- CB-H24-4S2M-2W-6R-P-R-TG1-6X8-RX-0000P
- CB-H24-4D2M-1S-4R-P-L-TG2-8X5-0-0E000
- CB-H24-2D2M-1A-3R-P-R-EXP-8X8-0-FE00P